



**JUST**<sup>TM</sup>  
REFRIGERATION

# SUPERMARKET

## supermarket - deli warmer



	CGDW1220	CGDW1830	CGDW2440
Height	1350mm	1350mm	1350mm
Width	1300mm	1910mm	2520mm
Depth	1100mm	1100mm	1100mm
Height (crated)	1590mm	1590mm	1590mm
Width (crated)	1420mm	2030mm	2650mm
Depth (crated)	1240mm	1240mm	1240mm
Weight – Nett	127kg	175kg	198kg
Weight – Crated	142kg	225kg	244kg
Display Area	0.78m <sup>2</sup>	1.37m <sup>2</sup>	1.728m <sup>2</sup>
Voltage	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz
Number of Elements	2	2	2
Wattage of Elements	1150 watts	1500 watts	2000 watts
Temperature Range	30° – 75°C (Dry Heat) 30° – 65°C (Wet Heat)	30° – 75°C (Dry Heat) 30° – 65°C (Wet Heat)	30° – 75°C (Dry Heat) 30° – 65°C (Wet Heat)
Number of Full Insert Divisions	3	5	7
Number of Third Insert Divisions	3	5	7

### features

- Front sliding glass for easy cleaning
- Aesthetically pleasing aluminium sections used
- Removable colour coded plastic bumper rail insert
- Adjustable feet for leveling cabinet
- Chromadeck exterior finish
- Stainless steel work top for extra durability
- Polyurethane foam injection
- Temperature regulation by thermostat
- Automatic element burn out protection
- Light switch
- Top rear sliding doors



#### emd equipped<sup>TM</sup>

Breakthrough technology replaces a conventional thermostat with an advanced electronic energy management system to cool quicker and maintain a more consistent temperature, while saving precious electricity.



#### green advantage<sup>TM</sup>

By combining EMD control with ECM fans, electronic expansion valves and high-performance coils, we are able to further reduce energy consumption while improving cooling performance.



#### low e cabinet<sup>TM</sup>

A superior combination of LED lighting, polyurethane insulation and low emissivity glass yields power savings around 40% lower than conventional refrigeration units.

